09/2021

Mod: E60/PM6T

Production code: FU60/60FTRE21

Diamond

series function 600
type ELECTRIC griddles / fry-top
électrique

model E 60

technical sheet
fiche technique

E60/PM6T

E60/PMCD6T

GENERALE DESCIPTION

Pressed working top in stainless steel AISI 304, 10/10 thick. Surface and cooking plate hermetically welded together in order to avoid gaps. Cooking plates in satin or glossy-chrome finishing (-CR models), available with flat, grooved and 2/3 flat 1/3 grooved surfaces; 10 mm sloping surface to easily collect grease. Pilot burners with piezoelectric lighting. Gas regulation with safety tap equipped with thermocouple or safety valve.
Chromed models equipped with safety thermostat.

+ Construction plus

- Cooking plates in satin or glossy-chrome finishing, available with flat, grooved and 2/3 flat 1/3 grooved surfaces
- 10 mm sloping surface to easily collect grease

+ Performance plus

- Pilot burners with piezoelectric lighting

+ Atouts de performance

- Allumage du brûleur pilote par piézo-électrique

Vue d'ensemble

Surface de travail réalisée en acier inox AISI 304 et épaisseur 10/10. Soudure hermétique des plaques au plan afin d'éviter interstices. Plaques lisses, nervurées ou mixtes 2/3 lisse et 1/3 nervurées réalisées en acier doux ou en acier chromé. Plaques inclinées de 10 mm pour faciliter la collecte des graisses. Allumage du brûleur pilote par piézo-électrique. Réglage de la température à travers un robinet de sécurité avec thermocouple ou valve de sécurité. Modèles chromés avec thermostat de sécurité.

+ Atouts de conception

- Plaques lisses, nervurées ou mixtes 2/3 lisse et 1/3 nervurées réalisées en acier doux ou en acier chromé.
- Plaques inclinées de 10 mm pour faciliter la collecte des graisses

	dimensions *dimensions*	cooking plate dimension *dimensions plaque de cuisson*	plate surface *surface de la plaque*	gas power *puissance gaz*	ELECTRIC POWER *Puissance éléctrique*
E60/PM6T	60X60X28	59,5x47	2/3 smooth 1/3 ribbed *2/3 lisse 1/3 nervurée*	10,4 kW	6 kw
E60/PMCD6T	60X60X28	59,5x47	2/3 smooth 1/3 ribbed chromed *2/3 lisse 1/3 nervurée chromé*	10,4 kW	6 kw

For all models exept -T: height regulation 50 mm
Pour tous les modèles: régulation en hauteur de 50 mm