

06/2018

# **Mod: ASD/50**

**Production code: F-50 (DIAMOND)**



# SPECIFICATIONS

<b>Type</b>	Squeezer machine of citric fruits	
<b>Output</b>	<b>MOD. F-50:</b>	20-25 fruits/
	<b>MOD. F-50-A:</b>	20-25 fruits/
<b>Feed</b>	<b>MOD. F-50:</b>	Loading the ramp of feeder
	<b>MOD.F-50-A:</b>	Loading the basket of the feeder.
<b>Power consumption</b>	<b>MOD. F-50:</b>	150 W
	<b>MOD. F-50-A:</b>	250 W
<b>Voltage</b>	240-230 V / 50-	
<b>Squeezer dimensions</b>	<b>MOD.F-50:</b>	735 mm x 260 mm x 430mm (Included feed ramp)
	<b>MOD.F-50-A:</b>	750mm x 330mm x 430mm (Included feeder)
<b>Weight</b>	<b>MOD. F-50:</b>	30 Kilograms
	<b>MOD. F-50-A:</b>	40 Kilograms
<b>Operating conditions</b>	Temperature: 10°C to 30°C	
<b>Humidity</b>	20% to 85%	
<b>Noise level</b>	The noise level during the operation of the machine the juicer F-50 model is inside the allowed limits for the R.D. 1316/89 about the workers protection in front of the derivative risks to the exhibition the noise during the work. Their maximum rateable this in 69,3 dB and the half is equal to 69,3 dB.	



As a part of our policy of continuous improvement, FRUCOSOL reserves the right to make design and specification changes for product improvement without prior notice. The performance specification figures indicated are nominal values of production units. There may be some deviation from these values in individual units.