09/2021

Mod: E65/PMCD7T

Production code: FU65/70FTRE-CR

Diamond

series function 650
type electric griddles / fry top électrique
model E65/...

technical sheet
fiche technique

- E65/PM7T
- E65/PM7T-230/3-
- E65/PMCD7T
- E65/PMCD7T-230/3

General description

Pressed working top in stainless steel AISI 304, 10/10 thick. Surface and cooking plate welded together in order to avoid gaps. Cooking plates in satin or glossy-chrome finishing (-CR models), available with flat, grooved and 2/3 flat 1/3 grooved surfaces; 10 mm sloping surface to easily collect grease. Cooking temperature monitored by thermostats. All chromed models are equipped with safety thermostat.

+ Construction plus

- Plates in satin or glossy-chrome finishing, available with flat, grooved and mixed finishing
- 10 mm sloping surface to easily collect grease

+ Performance plus

- Sloping surface and drainage channel on the plate, to easily collect grease

+ Atouts de performance

- La collecte des graisses est facilitée par les plaques inclinées et par la présence des caniveaux de drainage

Vue d'ensemble

Surface de travail réalisée en acier inox AISI 304 et épaisseur 10/10. Soudure hermétique des plaques au plan afin d'éviter interstices. Plaques lisses, nervurées ou mixtes 2/3 lisse et 1/3 nervurées réalisées en acier doux ou en acier chromé. Plaques inclinées de 10 mm pour faciliter la collecte des graisses. Réglage de la température thermostatique. Modèles équipés avec thermostat de sécurité.

+ Atouts de conception

- Plaques lisses, nervurées ou mixtes réalisées en acier doux ou en acier chromé
- Plaques inclinées de 10 mm pour faciliter la collecte des graisses

	dimensions *dimensions*	**cooking plate dimension** *dimensions plaque de cuisson*	**plate surface finishing** *surface de la plaque*	**electric power** *puissance électrique*
E65/PM7T	70x65x28	39,5x52	2/3 smooth 1/3 ribbed *2/3 lisse 1/3 nervurée*	9 kW 380-415V 3N 50-60Hz
E65/PMCD7T	70x65x28	39,5x52	2/3 smooth 1/3 ribbed chromed *2/3 lisse 1/3 nervurée*	9 kW 380-415V 3N 50-60Hz

For all models power also available at 220-240V 3 50-60Hz power
Pour tous les modèles sur demande avec puissance 220-240V 3 50-60Hz