

12/2018

Mod: AD1B/H-R2

Production code: AE07X2510-DM



Diamond
catering equipment

Modello - Model - Model - Gerätetyp		AD1B/H-R2	
Code Production		AE07X2510-DM	
Descrizione - Description - Description - Beschreibung		700 BT	
Tipo di teglie - Trays type - Type de plateaux - Blechtyp - Tipo de fuentes		GN 2/1	
Range		-22°C...-15°C	
Scheda Elettronica - Electronic card		EVCO EVX214	
Funzionamento - Operating Mode - Mode de fonctionnement - Betriebsmodus S = Statico - Static - Statique - Stille Kühlung - V = Ventilato - Ventilated - Ventilte - Umluftkühlung		V	
Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen		I	700
Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen			
Lunghezza - Width - Largeur - Breite		mm	770
Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tür		mm	820/1520
Altezza - Height - Hauteur - Höhe		mm	2025
Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen			
Lunghezza - Width - Largeur - Breite		mm	600
Profondità - Depth - Profondeur - Tiefe		mm	670
Altezza - Height - Hauteur - Höhe		mm	1440
Porte - Doors - Portes - Türen		1, Full	
Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter 530x650 3	
Luce interna - Internal light - Eclairage intérieure - Innerbeleuchtung		②	●
Serratura - Lock - Serrure - Schloss		②	●
Sbrinamento - Defrost - Dégivrage - Abtauen			
Type		Hot Gas	
N° Defrost in 24 hrs.		Automatic	
Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Automatic by Hot Gas	
Compressor			
Model		NEU2168U	
Potenza - Power - Puissance - Leistung		HP	3/4
T° Evaporation		°C	-10
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung		watt	600
Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp		GWP	R290 / 3
Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge		gr	130
Potenza assorbita - Total Power - Puissance - Leistung		watt	580W 2,9A / 840W 4A
Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung		V	230V~ 50Hz
220V/60Hz Voltage		<input type="checkbox"/>	
Peso Netto - Net weight - Poids net - Netto Gewicht		kg	140
Volume - Volume - Volume - Volumen		mc	1,5
Versione Predisposta - Remote version - Version sans groupe - Modelle ohne Aggregat Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtauerung		<input type="checkbox"/>	
Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse		D	
Energia - Energy - Énergie - Energie		kWh / annum	2355
Volume Netto - Net Volume - Volume Net - Nettoinhalt		I	458
Classe Climatica - Climate Class - Classe Climatique - Klima Klasse		5 40°C-40%	

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung = Optional

