

12/2018

# **Mod: AD2N/H2G-R2**

**Production code: AE14V2500-DM**



**Diamond**  
catering equipment

<b>Modello - Model - Model - Gerätetyp</b>		<b>AD2N/H2G-R2</b>
Code Production		AE14V2500-DM
<b>Descrizione - Description - Description - Beschreibung</b>		<b>1400 PVTN</b>
<b>Tipo di teglie - Trays type - Type de plateaux - Blechetyt - Tipo de fuentes</b>		GN 2/1
<b>Range</b>		0°C +10°C
<b>Scheda Elettronica - Electronic card</b>		EVCO EVX214
<b>Funzionamento - Operating Mode - Mode de fonctionnement - Betriebsmodus</b> <b>S = Statico - Static - Statique - Stille Kühlung - V = Ventilato - Ventilated - Ventilte - Umluftkühlung</b>		Ventilated
<b>Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen</b>		I 1400
<b>Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen</b>		
Lunghezza - Width - Largeur - Breite		mm 1500
Profondità / con porte aperte - Depth / with open doors / Profondeur avec portes ouverte - Tiefe/mit geöffneter Tür		mm 820/1520
Altezza - Height - Hauteur - Höhe		mm 2025
<b>Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen</b>		
Lunghezza - Width - Largeur - Breite		mm 1350
Profondità - Depth - Profondeur - Tiefe		mm 670
Altezza - Height - Hauteur - Höhe		mm 1440
<b>Porte - Doors - Portes - Türen</b>		2, Glass
<b>Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung</b>		Griglia plastificata - Plastic-Coated Grid Grille Plastifée - Kunststoff-Beschichtetes Gitter 530x650 3+3
<b>Luce interna - Internal light - Eclairage intérieure - Innerbeleuchtung</b>		② Full Glass Vertical Light
<b>Serratura - Lock - Serrure - Schloss</b>		② ●
<b>Sbrinamento - Defrost - Dégivrage - Abtauen</b>		
Type		Hot Gas
N° Defrost in 24 hrs.		Automatic
Evaporazione acqua sbrinamento - Evaporation of defrost water / Evaporation eau de dégivrage - Tauwasser verdunstung		Automatic by Hot Gas
<b>Compressor</b> <span style="float: right;">embraco</span>		
Model		NEU6210U
Potenza - Power - Puissance - Leistung		HP 1/3
T° Evaporation		°C -10
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung		watt 740
<b>Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp</b>		GWP R290 / 3
<b>Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge</b>		gr 100
<b>Potenza assorbita - Total Power - Puissance - Leistung</b>		watt 500W - 2,6A 700W - 4,9A
<b>Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung</b>		V 230V~ 50Hz
<b>220V/60Hz Voltage</b>		□
<b>Peso Netto - Net weight - Poids net - Netto Gewicht</b>		kg 289
<b>Volume - Volume - Volume - Volumen</b>		mc 49
<b>Versione Predisposta - Remote version - Version sans groupe - Modelle ohne Aggregat</b> Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtauerung		- - -
<b>Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse</b>		D
<b>Energia - Energy - Énergie - Energie</b>		kWh / annum 1675
<b>Volume Netto - Net Volume - Volume Net - Nettoinhalt</b>		I 1096
<b>Classe Climatica - Climate Class - Classe Climatique - Klima Klasse</b>		<b>4</b> 30°C-55%

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □ = Optional

