
























12/2018

Mod: AD2B/H2G-R2

Production code: AE14V2510-DM



Diamond
catering equipment

	Modello - Model - Model - Gerätetyp		AD2B/H2G-R2
		Code Production	AE14V2510-DM
			
	Descrizione - Description - Description - Beschreibung		1400 PVBT
	Tipo di teglie - Trays type - Type de plateaux - Blechetyp - Tipo de fuentes		GN 2/1
	Range		-20°C -10°C
	Scheda Elettronica - Electronic card		EVCO EVX214
	Funzionamento - Operating Mode - Mode de fonctionnement - Betriebsmodus S = Statico - Static - Statique - Stille Kühlung - V = Ventilato - Ventilated - Ventile - Umluftkühlung		V
	Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen	l	1400
	Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen		
	Lunghezza - Width - Largeur - Breite	mm	1500
	Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tür	mm	820/1520
	Altezza - Height - Hauteur - Höhe	mm	2025
	Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen		
	Lunghezza - Width - Largeur - Breite	mm	1350
	Profondità - Depth - Profondeur - Tiefe	mm	670
	Altezza - Height - Hauteur - Höhe	mm	1440
	Porte - Doors - Portes - Türen		2, Glass
	Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		Griglia plastificata - Plastic-Coated Grid Grille Plastifiée - Kunststoff-Beschichtetes Gitter 530x650 3+3
	Luce interna - Internal light - Eclairage intérieure - Innerbeleuchtung	②	Full Glass Vertical Light
	Serratura - Lock - Serrure - Schloss	②	●
	Sbrinamento - Defrost - Dégivrage - Abtauen		
	Type		Hot Gas
	N° Defrost in 24 hrs.		Automatic
	Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasser verdunstung		Automatic by Hot Gas
	Compressor	embraco	
	Model		NT2210U
	Potenza - Power - Puissance - Leistung	HP	1 - 1/4
	T° Evaporation	°C	-30
	Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	910
	Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp	GWP	R290 / 3
	Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge	gr	140
	Potenza assorbita - Total Power - Puissance - Leistung	watt	1050 - 5,1
	Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	230V~ 50Hz
	220V/60Hz Voltage		<input type="checkbox"/>
	Peso Netto - Net weight - Poids net - Netto Gewicht	kg	289
	Volume - Volume - Volume - Volumen	mc	2,9
	Versione Predisposta - Remote version - Version sans groupe - Modelle ohne Aggregat Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtauerung		- - -
	Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse		E
	Energia - Energy - Énergie - Energie	kWh / annum	5537
	Volume Netto - Net Volume - Volume Net - Nettoinhalt	l	1096
	Classe Climatica - Climate Class - Classe Climatique - Klima Klasse		4 30°C-55%

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung = Optional

