
























02/2019

Mod: AP1N/F64-R2

Production code: AE64X2500-DM



Diamond
catering equipment

 Modello - Model - Model - Gerätetyp		AP1N/F64-R2	
Code Production		AE64X2500-DM	
		 	
 Descrizione - Description - Description - Beschreibung		PA 60x40 TN	
Tipo di teglie - Trays type - Type de plateaux - Blechtyp - Tipo de fuentes		EN600x400	
 Range		-2°C +8°C	
 Scheda Elettronica - Electronic card		EVCO EVX214	
 Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus		Ventilated	
 Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen		I	720
 Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen			
Lunghezza - Width - Largeur - Breite		mm	790
Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü		mm	820/1543,5
Altezza - Height - Hauteur - Höhe		mm	2025
 Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen			
Lunghezza - Width - Largeur - Breite		mm	640
Profondità - Depth - Profondeur - Tiefe		mm	682,5
Altezza - Height - Hauteur - Höhe		mm	1440
 Porte - Doors - Portes - Türen		1, Full	
Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		20 coppie guide - 20 pairs of slides 20 glissieres - 20 paar führungen	
Capacità teglie - Pans capacity MAX - Capacité bacs - Backblechekapazität		n°27 600x400	
Interasse teglie - Pans pitch - Pas des bacs - Backblecheabsatz		mm	50
 Serratura - Lock - Serrure - Schloss		●	
 Sbrinamento - Defrost - Dégivrages - Abtauen			
Type		Hot Gas	
N° Defrost in 24 hrs.		Automatic	
Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Automatic by Hot Gas	
 Compressor		embraco	
Model		EMC3119U	
Potenza - Power - Puissance - Leistung		HP	1/4
T° Evaporation		°C	-10
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung		watt	425
 Refrigerante - Réfrigérant type - Réfrigérant type - Kältemitteltyp		GWP	R290 / 3
Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge		gr	80
 Potenza assorbita - Total Power - Puissance - Leistung		watt	190W 0,9A
Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung		V	230V~ 50Hz
220V/60Hz Voltage			
 Noise Level		dbA	49
 Peso Netto - Net weight - Poids net - Netto Gewicht		kg	140
 Versione Predisposta - Remote version - Version sans groupe - Modelle ohne Aggregat Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtaung		□	
 Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse		D	
 Energia - Energy - Énergie - Energie		kWh / annum	705
 Volume Netto - Net Volume - Volume Net - Nettoinhalt		I	486
 Classe Climatica - Climate Class - Classe Climatique - Klima Klasse		5 40°C-40%	

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □ = Optional

