

12/2018

Mod: AP1N/F86-R2

Production code: AE68X2500-DM



Diamond
catering equipment

Modello - Model - Model - Gerätetyp		AP1N/L86
Code Production		AE68X2500-DM
Descrizione - Description - Description - Beschreibung		PA 60x80 TN
Tipo di teglie - Trays type - Type de plateaux - Blechetyyp - Tipo de fuentes		EN600x800
Range		-2°C +8°C
Scheda Elettronica - Electronic card		EVCO EVX214
Funzionamento - Operating Mode - Mode de fonctionnemen - Betriebsmodus		Ventilated
Capacità lorda - Gross Capacity - Capacité brute - Bruttovolumen		I 850
Dimensioni esterne - External Dimension - Dimensions externes - ußenabmessungen		
Lunghezza - Width - Largeur - Breite		mm 790
Profondità / con porte aperte - Depth / with open doors / Profondeur avec portes ouverte - Tiefe/mit geöffneter Tü		mm 1000/1723,5
Altezza - Height - Hauteur - Höhe		mm 2025
Dimensioni interne - Internal Dimension - Dimensions internes - Innenabmessungen		
Lunghezza - Width - Largeur - Breite		mm 640
Profondità - Depth - Profondeur - Tiefe		mm 862,5
Altezza - Height - Hauteur - Höhe		mm 1390
Porte - Doors - Portes - Türen		1, Full
Dotazione Standard - Standard Equipment - Equipement standard - Standardausstattung		20 coppie guide - 20 pairs of slides / 20 glissieres - 20 paar führungen
Capacità teglie - Pans capacity MAX - Capacité bacs - Backblechekapazität		n°27 600x800
Interasse teglie - Pans pitch - Pas des bacs - Backblecheabsatz		mm 50
Serratura - Lock - Serrure - Schloss		●
Sbrinamento - Defrost - Dégivrages - Abtauen		
Type		Hot Gas
N° Defrost in 24 hrs.		Automatic
Evaporazione acqua sbrinamento - Evaporation of defrost water / Evaporation eau de dégivrage - Tauwasserverdunstung		Automatic by Hot Gas
Compressor embraco		
Model		EMT6165U
Potenza - Power - Puissance - Leistung		HP 1/3
T° Evaporation		°C -10
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung		watt 520
Refrigerante - Refrigerant type - Réfrigérant type - Kältemitteltyp		GWP R290 / 3
Quantità di refrigerante - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge		gr 90
Potenza assorbita - Total Power - Puissance - Leistung		watt 330W 2,1A / 350W 2,3A
Tensione alimentazione - Supply Voltage - Tension d'alimentation - Anschlussspannung		V 230V~ 50Hz
220V/60Hz Voltage		
Noise Level		dbA 53
Peso Netto - Net weight - Poids net - Netto Gewicht		kg 152
Versione Predisposta - Remote version - Version sans groupe - Modelle ohne Aggregat Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtaung		□
Efficienza Energetica - Energy Efficiency - Classe Énergie - Energieeffizienzklasse		C
Energia - Energy - Énergie - Energie		kWh / annum 796
Volume Netto - Net Volume - Volume Net - Nettoinhalt		I 648
Classe Climatica - Climate Class - Classe Climatique - Klima Klasse		5 40°C-40%

●= Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □=Optional

