

01/2019

# Mod: AR1N/H1-R2

Production code: ARL1X2500



**Diamond**  
catering equipment

Modello - Model - Model - Gerätetyp		ARL1X2500	ARL1V2500
<b>Descrizione</b> - Description - Description - Beschreibung		<b>1P TN</b>	<b>1PV TN</b>
<b>Range</b>		<b>0°C +10°C</b>	<b>+2°C +10°C</b>
<b>Funzionamento</b> - Operating Mode - Mode de fonctionnement - Betriebsmodus S = Statico - Static - Statique - Stille Kühlung / V = Ventilato - Ventilated - Ventil - Umluftkühlung		<b>V</b>	<b>V</b>
<b>Capacità lorda</b> - Gross Capacity - Capacité brute - Bruttovolumen	l	1250	1250
<b>Materiale Esterno</b> - External Material - Matériau Extérieur - Verstoff Außen		<b>304</b>	
<b>Dimensioni esterne</b> - External Dimension - Dimensions externes - ußenabmessungen			
Lunghezza - Width - Largeur - Breite	mm	900	900
Profondità / con porte aperte - Depth / with open doors Profondeur avec portes ouverte - Tiefe/ mit geöffneter Tü	mm	1060/1890	1060/1890
Altezza - Height - Hauteur - Höhe	mm	2260	2260
<b>Materiale Interno</b> - Internal Material - Matériau Intérieur - Verstoff Innen		<b>304</b>	
<b>Dimensioni interne</b> - Internal Dimension - Dimensions internes - Innenabmessungen			
Lunghezza - Width - Largeur - Breite	mm	740	740
Profondità - Depth - Profondeur - Tiefe	mm	920	920
Altezza - Height - Hauteur - Höhe	mm	1850	1850
<b>Porte</b> - Doors - Portes - Türen		1, Full	1, Glass
<b>Carrelli</b> - Trolleys - Chariots - Wagen		n°1 GN 2/1 - 60x80 H=183max	
<b>Luce interna</b> - Internal light - Eclairage intérieure - Innerbeleuchtung		-	●
<b>Serratura</b> - Lock - Serrure - Schloss		●	●
<b>Sbrinamento</b> - Defrost - Dégivrage - Abtauen			
Type		Hot Gas	Hot Gas
N° Defrost in 24 hrs.		3	3
Evaporazione acqua sbrinamento - Evaporation of defrost water Evaporation eau de dégivrage - Tauwasserverdunstung		Automatic by Hot Gas	Automatic by Hot Gas
<b>Compressor</b>	<b>embraco</b>		
Model		NEU6210U	
Potenza - Power - Puissance - Leistung	HP	1/3	
T° Evaporation	°C	-10	
Potenza frigorifera - Refrigerant Power - Puissance frigorifique - Kälteleistung	watt	740	
<b>Refrigerante</b> - Refrigerant type - Réfrigérant type - Kältemitteltyp		R290 / 3	
<b>Quantità di refrigerante</b> - Refrigerant quantity - Quantité de réfrigérant - Kältemittelmenge	gr	100	
<b>Classe Climatica</b> - Climate Class - Classe Climatique - Klima Klasse		<b>5 40°C-40%</b>	<b>4 30°C-55%</b>
<b>Potenza assorbita</b> - Total Power - Puissance - Leistung	watt	500W - 2,6A (700W - 4,9A)	
<b>Tensione alimentazione</b> - Supply Voltage - Tension d'alimentation - Anschlussspannung	V	230V~ 50Hz	
<b>Noise Level</b>	dbA	49	
<b>Peso Netto</b> - Net weight - Poids net - Netto Gewicht	kg		
<b>Modello predisposto</b> - Model without motor - Modèle sans moteur - Modelle ohne Aggregat Sbrinamento elettrico - Electrical defrosting - Dégivrage électrique - Elektrische Abtauung		<b>ARL1X1R00 - R134a</b>	<b>ARL1V1R00 - R134a</b>

● = Dotazione di serie - Standard equipment - Dotation standard - Serien Ausstattung □ = Optional

