



10/2021

Mod: N65/R316G-P9

Production code: 11121702-0-N-K

Model :	N65/R212G-P9	N65/R316G-P9
		
Description	2x GN2/3 Under Broiler Refrigerator Counter Diamond, Feet H95/155, R290	3x GN2/3 Under Broiler Refrigerator Counter Diamond, R290, Stainless steel back
Light	no	no
Key lock	no	no
Range (°C)	-2 +8	-2 +8
Operating Mode	Ventilated	Ventilated
External Dimensions		
Width (mm)	1200	1600
Depth/with open drawers (mm)	600 / 1195	600 / 1195
Worktop height (mm)	645-705	645-705
Internal Dimensions		
Width (mm)	780	1215
Depth (mm)	475	475
Height (mm)	410	410
Gross capacity (L)	152	237
Defrost		
Type of defrost	Automatic by time, stop compressor	Automatic by time, stop compressor
No. of defrost in 24h	4	4
Evaporation of defrost water	Hot gas	Hot gas
Compressor		
Brand	Huayi / Cubigel	Huayi / Cubigel
Model	NLY45RA_b	GLY45RA_b
Power (hp)	1/5	1/6
Cooling power (W)	357	220
Evaporation temp. / Condensation temp. (°C)	-10 / +45	-10 / +45
Climate class (Temp./RH)	5 (40°C - 40%)	5 (40°C - 40%)
Refrigerant		
Refrigerant fluid / GWP	R290 / 3	R290 / 3
Refrigerant charge (kg)	0,075	0,075
Electronic Controller		
Brand	Dixell	Dixell
Model	XR30CH	XR30CH
Electrical		
Power input (W/A)	177 / 0,87	177 / 0,87
Power supply (V/Hz)	220-240/50	220-240/50
220V/60Hz	no	no
Packaging details		
Packed volume (m³)	0,73	0,98
Gross weight (kg)	100	160
Net weight (kg)	85	145
Efficiency Information		
Energy efficiency class	B	C
Daily Energy Consumption (E24h) (kWh)	1,50	2,20
Annual Energy Consumption (AEC) (kWh)	548	803
Net volume (L)	106	159
Climate class	4	4