





07/2015

Mod: ASM/185

Production code: 10404201-0-0-0 (V4 1850)



Diamond
catering equipment

Model	ASM/185	UAC/P1	ASM/200	UAC/P1
				
Production code	10404201-0-0-0	10402703-0-0-0	10404202-0-0-0	10402703-0-0-0
Description	Mini Cold Room	Monoblock Cooling Unit	Mini Cold Room	Monoblock Cooling Unit
No. and type of doors	1 Full	–	1 Full	–
No. and type of grid shelves	2	–	3	–
Light	no	–	no	–
Key lock	no	–	no	–
Range (°C)	–	+2° + 8°	–	+2° + 8°
Operating Mode	–	Ventilated	–	Ventilated
External Dimensions				
Width (mm)	935	675	935	675
Depth/with open doors (mm)	995 / 1872	495	995 / 1872	495
Height (mm)	1842	388	1992	388
Internal Dimensions				
Width (mm)	855	–	855	–
Depth (mm)	885	–	885	–
Height (mm)	1762	–	1912	–
Gross capacity (L)	1850	–	2000	–
Defrost				
Type of defrost	–	By time	–	By time
No. of defrost in 24h	–	6	–	6
Evaporation of defrost water	–	Hot gas	–	Hot gas
Compressor				
Brand	–	Tecumseh	–	Tecumseh
Model	–	AE 4430 Y	–	AE 4430 Y
Power (hp)	–	–	–	–
Cooling power (W)	–	445	–	445
Evaporation temp. (°C)	–	-15	–	-15
Climate class (°C)	–	+32	–	+32
Refrigerant				
Type	–	R134a	–	R134a
Refrigerant quantity (g)	–	250	–	250
Electronic Controller				
Brand	–	Dixell	–	Dixell
Model	–	XR30CH	–	XR30CH
Electrical				
Power input (W/A)	–	510 / 3,45	–	510 / 3,45
Power supply (V/Hz)	–	230/50	–	230/50
220V/60Hz	–	no	–	no
Packaging Details				
Packed volume (m ³)	1,24	0,20	1,24	0,20
Gross weight (kg)	153	33	165	33
Net weight (kg)	122	28	134	28