

05/2018

Mod: E9/6PQA12

Production code: BBE698AQ



Diamond
catering equipment

E698AQ

6 SQUARE PLATES ON OPEN STAND



SEE MORE TECHNICAL DATA:

External dimensions - WxDxH (cm)	120x90x85
Nr. Plates 3 kW	4
Nr. Plates 4 kW	2
Total power (kW)	20

HIDE THE OTHER TECHNICAL DATA:

Supply (N)	400V 3N 50/60Hz
Weight (kg)	126
Volume (m3)	1,4

The watertight pressed worktop is in 2 mm AISI 304 stainless steel. The fast-heating hot plates with safety device to prevent overheating, made in cast iron 300x300 mm, are watertight fixed to the worktop and are powered by 3 kW and 4 kW heating elements with 6 (+1) positions thermostat for optimized power control. Indicator lights show when each hotplate is in operation. Rounded corners and a moulded recess trap prevent overflowing, ensuring also easier cleaning. Versions with GN 2/1 static oven (electric heating): stainless steel double-wall cooking chamber with enameled bottom (optional cast iron bottom), stainless steel double-wall door with insulating casing. The electric oven has 6.2 kW stainless steel armoured heating elements placed on the bottom and on the top of the cooking chamber; thermostatic temperature control with separate bottom/ top temperature control for maximum cooking flexibility.

